

Product Specification

Product Name : ESC

Product Model: STONE 80A-MC

Version : V2.0

Date : 2024-12-13

NanChang ChangKong Technology Co., Ltd

I. PURPOSE

This product specification for the product in the production, testing and sales of the chain of norms to follow.

II. Scope of application

ESC, Used for input voltage: 20-61V DC.

III. Technical parameters

Item	Requirements	Remarks
Support lithium battery	6-14S(Above 65V prohibits startup)	Factory Inspection Items
Continuous operating current	80A	Specific thermal conditions
Instantaneous operating current (less than 3 seconds)	130A	
BEC Output Voltage	none	
Operating temperature	-20~+65°C	
Operating humidity	15%-85%RH	
preservation temperature	-10~+40°C	
Preservation of humidity	15%-65%RH	
waterproof rating	IP55	
Standby power consumption	≤10mA@60V	Factory Inspection Items
Throttle travel range	1000-2000us(default value)	calibratable
Throttle calibration range	maximum throttle(1.6-2.4ms), minimum throttle(0.6-1.4ms)	
Maximum supported speed	125,000 turn(Electrical RPM)	Mechanical RPM=Electrical RPM/polar logarithm
Throttle Refresh Frequency	50-500Hz(suggestion100-400Hz)	PWM low level>0.2ms
Starting Throttle Point	6.7%	
*Throttle Response Time	200ms(Default, customizable)	Throttle from idle to max
temperature protection point	125°C	
Input Signal Level	3.3-5V	
ESC weights	112g	± 2g
Product Size	90.4*36*18.5mm	± 0.1mm

* Specific heat dissipation conditions (low ambient temperature, blowing air, auxiliary cooling surface, feedback MOS temperature below 125 °C), you can continue to run 80A, continuous high temperature work will reduce the ESC service life, it is recommended to keep the feedback MOS temperature below 105°C in practical applications.

* Throttle response time: When ESC receives 10%~100% step throttle, the throttle reaches the maximum value within the specified time, but usually the motor speed lags behind the throttle by 100-150ms. (

NanChang ChangKong Technology Co., Ltd

Customized performance parameters are available, including protection temperature, response time, etc.)
 100-150ms. (Performance parameters can be customized according to customer needs, including but not limited
 To protection temperature, response time, etc.)

IV. Main material/part specifications

Item	Requirements	Remarks
Power cord specifications	12AWG	Factory Inspection Items
Power cord length	150 ± 5mm	
Power cord color	Red (Positive) Black (Negative)	
Output phase wire specification	14AWG	
Output phase cable length	100 ± 5mm	
Signal Cable Specification	UL1533-24AWG-Gray	
Signal Cable Length	540 ± 5mm	
Data Feedback Cable Specification	PVC cable - 30 cores - black red white	
Data Feedback Cable Length	80 ± 5mm	
Housing Material	Aviation aluminum alloy Surface anodized	

V. Structural dimensional drawings

